



CS6369
50A,
125/250V
power
outlet.



FEATURES:

- Power inlet & outlet clearly marked on lid for quick identification
- Heavy-duty safety yellow powder-coated enclosure
- Each NEMA 5-20 outlet is individually GFCI protected with open neutral protection
- 50A, 125/250V power inlet
- Automatic power-up GFCIs are ready immediately
Only need to push reset after a trip
- Heavy-duty powder-coated steel skids to insure rugged, dependable jobsite performance
- Flip covers protects outlets from damage & the weather
- A variety of accessories are available
- Unit is field repairable by qualified personnel. Parts list and wiring diagram appear on underside of lid
- Product label with clear markings for easy identification of model number, serial number and specifications

Typical Applications Include:

- Industrial, commercial and residential construction projects
- General maintenance and repair work (MRO) in industrial facilities
- Temporary power distribution at carnivals, circuses, fairs & similar events
- Convention centers to distribute power for exhibitions & maintenance
- Photo studios to distribute power to flash & other photographic equipment



Selection Guide

Catalog Number	1066	1066-B	1066FS	1066-BFS
Electrical Rating	50A 125/250V 6250W/12500W	50A 125/250V 6250W/12500W	50A 125/250V 6250W/12500W	50A 125/250V 6250W/12500W
Enclosure	Steel Welded Powder Coated	Steel Welded Powder Coated	Steel Welded Powder Coated	Steel Welded Powder Coated
Environmental/NEMA Rating	Indoor Use Only	Indoor Use Only	Indoor/Outdoor 3R	Indoor/Outdoor 3R
Receptacles				
A Type (6 per box)	NEMA 5-20 T Slot Duplex (125V 20A)	NEMA 5-20 T Slot Duplex (125V 20A)	NEMA 5-20 T Slot Duplex (125V 20A)	NEMA 5-20 T Slot Duplex (125V 20A)
Qty.	6	6	6	6
GFCI Protection	Yes	Yes	Yes	Yes
Overload Protection	Yes - 1P 20A C.B. (1 per Duplex)	Yes - 1P 20A C.B. (1 per Duplex)	Yes - 1P 20A C.B. (1 per Duplex)	Yes - 1P 20A C.B. (1 per Duplex)
Flip Covers	No	No	Yes	Yes
B Type (1 Per Box)	L6-30 (30A, 250V)	L6-30 (30A, 250V)	L6-30 (30A, 250V)	L6-30 (30A, 250V)
Qty.	1	1	1	1
240V GFCI Protection	No	Yes	No	Yes
Overload Protection	Yes - 2P NON-GFCI	Yes - 2P GFCI	Yes - 2P NON-GFCI	Yes - 2P GFCI
Flip Covers	No	No	Yes	Yes
Main Power Inlet	4W CS6375 (50A,125/250V)	4W CS6375 (50A,125/250V)	4W CS6375 (50A,125/250V)	4W CS6375 (50A,125/250V)
Inlet Flip Cover	No	No	Yes	Yes
Main Power Outlet (Mains Feed Thru)	4W CS6369 (50A,125/250V)	4W CS6369 (50A,125/250V)	4W CS6369 (50A,125/250V)	4W CS6369 (50A,125/250V)
Mains Feed thru Flip Cover	Yes	Yes	Yes	Yes
Weight (lbs.)	34	34	36	36
Dimensions	22.5"L x 16.25"W x 11.75"H	22.5"L x 16.25"W x 11.75"H	22.5"L x 16.25"W x 11.75"H	22.5"L x 16.25"W x 11.75"H

Notes: Contact factory for custom assemblies

Accessories

Cat. Number	Description
63DSO ⁽¹⁾	Cord set, 100', #6/3 - 8/1 SO 50A 125V/250V
63BSO ⁽¹⁾	Cord set, 50', #6/3 - 8/1 SO 50A 125V/250V
SR50	Power Outlet Receptacle in weatherproof box with lift cover and 24" leads 50A, 125V/250V

Note: ⁽¹⁾ Also available as a secondary cable assembly - cord with connector only - to hard wire into your power source.



See Our Complete Line of 50Amp Power Cords in the Power Cord Section

